

DUNNAGE BAG AIR BAGS

PRODUCT LIST

Common Size Dunnage Bags (L0, L1, L2, L3, L4, L5)			
Size (inch)	Size (cm)	Void Size (inch)	Void Size (cm)
24 x 24	60 x 60	8	20
24 x 36	60 x 90	8	20
24 x 48	60 x 120	8	20
24 x 60	60 x 150	8	20
24 x 66	60 x 165	8	20
36 x 36	90 x 90	12	30
36 x 48	90 x 120	12	30
36 x 60	90 x 150	12	30
36 x 66	90 x 165	12	30
36 x 72	90 x 180	12	30
36 x 84	90 x 210	12	30
36 x 96	90 x 240	12	30
36 x 102	90 x 260	12	30
40 x 40	100 x 100	14	35
40 x 48	100 x 120	14	35
48 x 48	120 x 120	16	40
48 x 60	120 x 150	16	40
48 x 66	120 x 165	16	40
48 x 72	120 x 180	16	40
48 x 84	120 x 210	16	40
48 x 96	120 x 240	16	40
48 x 102	120 x 260	16	40

*Any other sizes will be supplied upon request.

*Type of the valves and valve positions can be changed upon request.

DUNNAGE BAG / LEVEL 0

It is designed for filling the lateral voids, basically in truck and lorry transportation.
It provides protection for products in bumpy land road transportation.

Level	Max. Pressure	Application	Transportation Mode
Show L0	2 PSI	Lateral Void	Road Only (Truck/Lorry)

DUNNAGE BAG / LEVEL 1

It is designed for filling the lateral voids, basically for lorry and container transportation.
It provides protection for products in bumpy land road transportation.

Level	Max. Pressure	Application	Transportation Mode
Show L1	2.5 PSI	Lateral Void	Road/Intermodal (Lorry/Container)

DUNNAGE BAG / LEVEL 2

It is designed for railway wagon and container loads weighing up to 33,750 Kg.
Balances pressure on the cargo in railways during braking and vibration.

Level	Max. Pressure	Application	Transportation Mode
Show L2	3-4 PSI	Lengthwise Void	Rail/Intermodal

DUNNAGE BAG / LEVEL 3

It is designed for railway wagon and container loads weighing up to 72,000 Kg.
Balances pressure on the cargo in railways and roads during braking and vibration.

Level	Max. Pressure	Application	Transportation Mode
Show L3	6 PSI	Lengthwise Void	Rail/Intermodal

DUNNAGE BAG / LEVEL 4

It is designed for the voids in wagons, vessels and containers weighing up to 85,000 Kg.
Protects against possible damage to the cargo in bulk vessel loading, heavy and weight Rail ways transportation

Level	Max. Pressure	Application	Transportation Mode
Show L4	8 PSI	Lengthwise/ Horizontal in Void	Rail/Marine

DUNNAGE BAG / LEVEL 5

It is designed for the voids in wagons, vessels and containers weighing up to 97,000 Kg.
Protects against possible damage to the cargo in bulk vessel loading, heavy and weight railways transportation

Level	Max. Pressure	Application	Transportation Mode
Show L5	10 PSI	Lengthwise/ Horizontal in Void	Rail/Marine



DUNNAGE BAG PAZARLAMA SANAYİ VE TİCARET LİMİTED ŞİRKETİ
Ostim 1137. Cad. 16602 Ada Keresteciler Sit. Yenimahalle / Ankara
Phone: +90 532 701 98 16 Fax: 0 312 395 90 21